



WEVER & DUCRÉ  
LIGHTING

# RAY SUSPENDED 2.0 LED

217164L3

Project
Type
Notes
Quantity
Date

## GENERAL

Ceiling  
Suspended  
Aluminium Brushed  
IP20  
Interior  
405 lm

## LED

2700 K  
CRI 90  
L80 / 50000 h  
3-step binning  
MR 0.53  
MDER 0.48

## OPTICAL


Beam angle 35°

## PHYSICAL


Diameter 67 mm  
Height 200 mm  
0.62 kg  
incl. 2.5 m suspension

## ELECTRICAL


phase-cut dim  
220 - 240 V  
Total connected power 5.5 W  
PC1  
Safety distance 0.3 m



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Aluminium Brushed; wet painted; inclusive adjustable cable suspension max. 2500mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; phase-cut dim; light colour 2700 K; Binning initial 3 MacAdam; CRI 90; 220 - 240 V; degree of protection IP20; PC1; power supply included; ceiling base not included; light source replaceable by end-user; control gear replaceable by end-user;



## LIGHT DISTRIBUTION





**WEVER & DUCRÉ**  
LIGHTING

# RAY

## SUSPENDED 2.0 LED

217164L3

### CONE DIAGRAM


35°

h (m)	E0° (lx)	ø (m)
1	999	0.63
2	250	1.26
3	111	1.89
4	62	2.52
5	40	3.15

### SUSPENSION OPTIONS

#### Invisible Ceiling Suspension System

COLOUR	L · W (MM)	ORDERCODE
Black	140 · 66	9 0 0 1 5 1 9 5
White	140 · 66	9 0 0 1 5 1 9 6



#### Single Suspension

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
Ceiling Base round	Black	ø84 · 29	9 0 0 5 2 0 2 1
Ceiling Base round	White	ø84 · 29	9 0 0 5 2 0 2 2



#### Single Ceiling Base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
semi recessed	White	ø84 · 72	9 0 0 5 2 0 2 6
semi recessed	Black	ø84 · 72	9 0 0 5 2 0 2 7

