



WEVER & DUCRÉ  
LIGHTING

# RAY SUSPENDED 2.0 LED

226764G3

Project
Type
Notes
Quantity
Date

## GENERAL

Ceiling , Suspended  
 Gold  
 IP20  
 Interior  
 Output: 405 lm  
 CIE flux code: 98 100 100 100 100

## LED

2700 K  
 CRI ≥ 90  
 L80 / 50000 h  
 2 SDCM

## OPTICAL

Beam angle 36°

## ELECTRICAL


phase-cut dim  
 220 - 240 V  
 Total connected power 5.5 W  
 Class 1

## PHYSICAL


Diameter 67 mm  
 Height 200 mm  
 0.62 kg  
 incl. 4.0 m suspension



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Gold; wet painted; brushed; inclusive adjustable cable suspension max. 2500mm in Signal Black; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP20; PC1; driver included; ceiling base not included; light source replaceable by an authorized professional; control gear replaceable by end-user;



## LIGHT DISTRIBUTION



[226764G3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.  
 © Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# RAY SUSPENDED 2.0 LED

226764G3

## CONE DIAGRAM

35°

h (m)	E0° (lx)	ø (m)
1	994	0.63
2	249	1.26
3	110	1.89
4	62	2.52
5	40	3.15

## SINGLE SUSPENSION

### Invisible ceiling base

COLOUR	L · W (MM)	ORDERCODE
Black	140 · 66	9 0 0 1 5 1 9 5
White	140 · 66	9 0 0 1 5 1 9 6



### Single base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ceiling base round	Black	ø84 · 29	9 0 0 5 2 0 2 1
ceiling base round	White	ø84 · 29	9 0 0 5 2 0 2 2

### Semi recessed base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for shades without steel wire only	White	ø84 · 72	9 0 0 5 2 0 2 6
for shades without steel wire only	Black	ø84 · 72	9 0 0 5 2 0 2 7

## WALL BASE

### WALL BASE

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for 1 luminaire	White	ø82 · 32	9 0 0 1 9 1 9 5
for 1 luminaire	Black	ø82 · 32	9 0 0 1 9 1 9 6

### Cable Wall-Ceiling Bracket

COLOUR	Ø · H (MM)	ORDERCODE
White	ø16 · 30	9 0 0 1 9 1 9 7
Black	ø16 · 30	9 0 0 1 9 1 9 8



WEVER & DUCRÉ  
LIGHTING

# RAY SUSPENDED 2.0 LED

226764G3

## MULTI SUSPENSION

### Multiple base round

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
up to max. 4 luminaires	White	Ø123·44	9 0 0 5 2 0 0 5
up to max. 4 luminaires	Black	Ø123·44	9 0 0 5 2 0 0 6
up to max. 8 luminaires	White	Ø123·44	9 0 0 5 2 0 3 1
up to max. 8 luminaires	Black	Ø123·44	9 0 0 5 2 0 3 2

### Multiple base linear

TYPE	COLOUR	L·W·H (MM)	ORDERCODE
up to max. 2 luminaires	White	600·30·45	9 0 0 5 2 0 0 7
up to max. 2 luminaires	Black	600·30·45	9 0 0 5 2 0 0 8
up to max. 3 luminaires	White	900·30·45	9 0 0 5 2 0 0 9
up to max. 3 luminaires	Black	900·30·45	9 0 0 5 2 0 1 0
up to max. 4 luminaires	White	1200·30·45	9 0 0 5 2 0 1 1
up to max. 4 luminaires	Black	1200·30·45	9 0 0 5 2 0 1 2
up to max. 5 luminaires	White	1500·30·45	9 0 0 5 2 0 1 3
up to max. 5 luminaires	Black	1500·30·45	9 0 0 5 2 0 1 4

## OPTIONAL

### Hook

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
standard multi suspension hook	Black	Ø3·83	9 0 0 5 2 0 2 4
standard multi suspension hook	White	Ø3·83	9 0 0 5 2 0 2 5
optional multi suspension hook	Black	Ø5·90	9 0 0 5 2 0 6 5
optional multi suspension hook	White	Ø5·90	9 0 0 5 2 0 6 6
for cable 4.25-5.5mm diameter	White	Ø15·35	9 0 0 5 2 0 7 9
for cable 4.25-5.5mm diameter	Black	Ø15·35	9 0 0 5 2 0 8 0