



WEVER & DUCRÉ
LIGHTING

RAY SUSPENDED 3.0 LED

226864W3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling, Suspended

White Matt

RAL 9003^a

IP20

Interior

Output: 405 lm

CIE flux code: 98 100 100 100 100

LED

2700 K

CRI ≥ 90

L80 / 50000 h

2 SDCM

OPTICAL

Beam angle 36°

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 5.5 W

Class 1

PHYSICAL

Diameter 67 mm

Height 300 mm

0.76 kg

incl. 4.0 m suspension

^a Color may deviate slightly due to production conditions.



Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface White Matt; powder coated; matt texture; RAL 9003; inclusive adjustable cable suspension max. 2500mm in Pure White; with COB (Chip on Board) technology for maximum efficiency; phase-cut dim; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; 220 - 240 V; degree of protection IP20; PC1; driver included; ceiling base not included; light source replaceable by an authorized professional; control gear replaceable by end-user;






WEVER & DUCRÉ
LIGHTING

RAY SUSPENDED 3.0 LED

226864W3

LIGHT DISTRIBUTION



CONE DIAGRAM

35°

h (m)	E0° (lx)	ø (m)
1	994	0.63
2	249	1.26
3	110	1.89
4	62	2.52
5	40	3.15

SINGLE SUSPENSION

Invisible ceiling base

COLOUR	L · W (MM)	ORDERCODE
Black	140-66	9 0 0 1 5 1 9 5
White	140-66	9 0 0 1 5 1 9 6



Single base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
ceiling base round	Black	ø84-29	9 0 0 5 2 0 2 1
ceiling base round	White	ø84-29	9 0 0 5 2 0 2 2

Semi recessed base

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for shades without steel wire only	White	ø84-72	9 0 0 5 2 0 2 6
for shades without steel wire only	Black	ø84-72	9 0 0 5 2 0 2 7

WALL BASE

WALL BASE

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
for 1 luminaire	White	ø82-32	9 0 0 1 9 1 9 5
for 1 luminaire	Black	ø82-32	9 0 0 1 9 1 9 6

[226864W3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com

August 25, 2023



WEVER & DUCRÉ
LIGHTING

RAY SUSPENDED 3.0 LED

226864W3

Cable Wall-Ceiling Bracket

COLOUR	Ø · H (MM)	ORDERCODE
White	∅16-30	9 0 0 1 9 1 9 7
Black	∅16-30	9 0 0 1 9 1 9 8

MULTI SUSPENSION

Multiple base round

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
up to max. 4 luminaires	White	∅123-44	9 0 0 5 2 0 0 5
up to max. 4 luminaires	Black	∅123-44	9 0 0 5 2 0 0 6
up to max. 8 luminaires	White	∅123-44	9 0 0 5 2 0 3 1
up to max. 8 luminaires	Black	∅123-44	9 0 0 5 2 0 3 2

Multiple base linear

TYPE	COLOUR	L · W · H (MM)	ORDERCODE
up to max. 2 luminaires	White	600-30-45	9 0 0 5 2 0 0 7
up to max. 2 luminaires	Black	600-30-45	9 0 0 5 2 0 0 8
up to max. 3 luminaires	White	900-30-45	9 0 0 5 2 0 0 9
up to max. 3 luminaires	Black	900-30-45	9 0 0 5 2 0 1 0
up to max. 4 luminaires	White	1200-30-45	9 0 0 5 2 0 1 1
up to max. 4 luminaires	Black	1200-30-45	9 0 0 5 2 0 1 2
up to max. 5 luminaires	White	1500-30-45	9 0 0 5 2 0 1 3
up to max. 5 luminaires	Black	1500-30-45	9 0 0 5 2 0 1 4

OPTIONAL

Hook

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
standard multi suspension hook	Black	∅3-83	9 0 0 5 2 0 2 4
standard multi suspension hook	White	∅3-83	9 0 0 5 2 0 2 5
optional multi suspension hook	Black	∅5-90	9 0 0 5 2 0 6 5
optional multi suspension hook	White	∅5-90	9 0 0 5 2 0 6 6
for cable 4.25-5.5mm diameter	White	∅15-35	9 0 0 5 2 0 7 9
for cable 4.25-5.5mm diameter	Black	∅15-35	9 0 0 5 2 0 8 0