

RAYSUSPENDED 3.0 PAR16

217220B0

Project
Type
Notes
Quantity
Date

GENERAL
Ceiling
Suspended
Jet Black
IP20
Interior
440 ^a to 445 ^b lm
RAL 9005 ^c
LED
Lamp PAR16
PAR16
Socket GU10
max. 12 W
CRI 80
OPTICAL
Beam angle 48°
PHYSICAL
Diameter 67 mm
Height 300 mm
0.68 kg
incl. 2.5 m suspension
ELECTRICAL
100 - 240 V
1

Total connected power 6.6^{b} to 6.7^{a} W

^c RAL Palette colors may deviate slightly due


Safety distance 0.3 m

 $^{\rm a}$ LED 3000K CRI 80 white $^{\rm b}$ LED 2700K CRI 80 white


 $to\ production\ conditions.$

(1)	_	§ ←0,3→

Cylindrical ceiling suspended luminaire made from die-cast aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; inclusive adjustable cable suspension max. 2500mm in Signal Black; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; degree of protection IP20; PC1; lamp not included; ceiling base not included;



LIGHT DISTRIBUTION



January 14, 2022



RAYSUSPENDED 3.0 PAR16

217220B0

CONE DIAGRAM

LED 2700K CRI ≥ 8408 % white

h (m)	E0° (lx)	ø (m)
1	626	0.89
2	157	1.78
3	70	2.67
4	39	3.56
5	25	4.45

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø⋅H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50·58	901228B3
3000K >90 CRI GU10	Black	ø50·58	901228B5
2700K >80 CRI GU10	White	ø50·58	901228W2
2700K >90 CRI GU10	White	ø50·58	901228W3
3000K >80 CRI GU10	White	ø50·58	901228W4
2700K >80 CRI GU10	Silver	ø51·55	905227S2
3000K >80 CRI GU10	Silver	ø51·55	90522784

SUSPENSION OPTIONS

Invisible Ceiling Suspension System

COLOUR	L·W (MM)	ORDERCODE
Black	140.66	90015195
White	140.66	90015196



Single Suspension

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
Ceiling Base round	Black	Ø84·29	90052021
Ceiling Base round	White	Ø84·29	$9\ 0\ 0\ 5\ 2\ 0\ 2\ 2$



Single Ceiling Base

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
semi recessed	White	Ø84·72	90052026
semi recessed	Black	Ø84·72	90052027



January 14, 2022