



WEVER & DUCRÉ  
LIGHTING

# RAY WALL mini 1.0

300220B0

Project
Type
Notes
Quantity
Date

## GENERAL

Wall  
 Surface  
 Jet Black  
 IP20  
 Interior  
 440<sup>a</sup> to 445<sup>b</sup> lm  
 RAL 9005<sup>c</sup>

## LED

Lamp PAR16  
 PAR16  
 Socket GU10  
 max. 12 W  
 CRI 80

## OPTICAL

Beam angle 48°  
 UGR < 19  
 65° < 3000 cd/m<sup>2</sup>


## PHYSICAL

Diameter 67 mm  
 Height 115 mm  
 0.21 kg


## ELECTRICAL

100 - 240 V  
 Total connected power 6.6<sup>b</sup> to 6.7<sup>a</sup> W  
 PC1  
 Safety distance 0.3 m


<sup>a</sup> LED 3000K CRI 80 white  
<sup>b</sup> LED 2700K CRI 80 white  
<sup>c</sup> RAL Palette colors may deviate slightly due to production conditions.



Cylindrical wall surface mounted luminaire made from aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; direct light distribution; lamp socket GU10; lamp type PAR16; max. 12W; 100 - 240 V; lamp not included; degree of protection IP20; PC1;



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# RAY

## WALL mini 1.0

300220B0

### LED LAMPS

#### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   >90 CRI   GU10	Black	∅50·58	9 0 1 2 2 8 B 3
3000K   >90 CRI   GU10	Black	∅50·58	9 0 1 2 2 8 B 5
2700K   >80 CRI   GU10	White	∅50·58	9 0 1 2 2 8 W 2
2700K   >90 CRI   GU10	White	∅50·58	9 0 1 2 2 8 W 3
3000K   >80 CRI   GU10	White	∅50·58	9 0 1 2 2 8 W 4
2700K   >80 CRI   GU10	Silver	∅51·55	9 0 5 2 2 7 S 2
3000K   >80 CRI   GU10	Silver	∅51·55	9 0 5 2 2 7 S 4