



WEVER & DUCRÉ
LIGHTING

RAY

WALL mini 2.0

301220B0

Project

Type

Notes

Quantity

Date

GENERAL

Wall
Surface
Jet Black
IP20
Interior
Indirect 440^a to 445^b lm
Direct 440^a to 445^b lm
Total 880^a to 890^b lm
RAL 9005^c

LED

Lamp 2 x PAR16
PAR16
Socket GU10
max. 12 W
CRI 80

OPTICAL

Beam angle 360°
UGR < 13
65° < 3000 cd/m²

PHYSICAL

Diameter 67 mm
Height 200 mm
0.36 kg


ELECTRICAL

100 - 240 V
Total connected power 13.2^b to 13.3^a W
PC1
Safety distance 0.3 m


^a LED 3000K CRI 80 white

^b LED 2700K CRI 80 white


^c RAL Palette colors may deviate slightly due to production conditions.



Cylindrical wall surface mounted luminaire made from aluminium; surface Jet Black; powder coated; matt texture; RAL 9005; direct/indirect light distribution; lamp socket GU10; lamp type PAR16; 2x max. 12W; 100 - 240 V; lamp not included; degree of protection IP20; PC1;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

RAY

WALL mini 2.0

301220B0

LED LAMPS

PAR16 LED Lamp

| TYPE | COLOUR | Ø·H (MM) | ORDERCODE |
|------------------------|--------|----------|-----------------|
| 2700K >90 CRI GU10 | Black | ø50·58 | 9 0 1 2 2 8 B 3 |
| 3000K >90 CRI GU10 | Black | ø50·58 | 9 0 1 2 2 8 B 5 |
| 2700K >80 CRI GU10 | White | ø50·58 | 9 0 1 2 2 8 W 2 |
| 2700K >90 CRI GU10 | White | ø50·58 | 9 0 1 2 2 8 W 3 |
| 3000K >80 CRI GU10 | White | ø50·58 | 9 0 1 2 2 8 W 4 |
| 2700K >80 CRI GU10 | Silver | ø51·55 | 9 0 5 2 2 7 S 2 |
| 3000K >80 CRI GU10 | Silver | ø51·55 | 9 0 5 2 2 7 S 4 |