



WEVER & DUCRÉ
LIGHTING

RAY

WALL mini 2.0

301220B0

Project

Type

Notes

Quantity

Date

GENERAL

Wall , Surface

Black Matt

RAL 9011^a

IP20

Interior

Indirect 440^b to 445^c lm

Direct 445^b to 465^c lm

Total 885^b to 910^c lm

CIE flux code: 96 99 100 50 96

LED

Lamp 2 x PAR16

Socket GU10

max. 12.0 W

2700 K^b, 3000 K^c

CRI ≥ 90

OPTICAL

Wide Flood , Beam angle 360°

UGR < 13

≥3000 cd/m²

ELECTRICAL

100 - 240 V

LED Inset 13.1^c to 13.2^b W

Class 1

PHYSICAL

Diameter 67 mm

Height 200 mm

0.36 kg


^a Color may deviate slightly due to production conditions.

^b PAR16 LAMP 2700K CRI90


^c PAR16 LAMP 3000K CRI90



Cylindrical wall surface mounted luminaire made from aluminium; surface Black Matt; powder coated; matt texture; RAL 9011; direct/indirect light distribution; lamp socket GU10; lamp type PAR16; 2x max. 12W; 100 - 240 V; lamp not included; degree of protection IP20; PC1;



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

RAY

WALL mini 2.0

301220B0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	ø50·60	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Black	ø50·60	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	White	ø50·60	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	White	ø50·60	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Silver	ø50·60	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver	ø50·60	9 0 5 2 2 7 S 4