



WEVER & DUCRÉ
LIGHTING

RAY OUTDOOR 1.0

735364W4

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Signal White

IP65

Exterior

560 lm

RAL 9003^a

LED

3000 K

CRI 80

L70 / 50000 h

3-step binning

OPTICAL

Flood

Beam angle 32°

PHYSICAL

Diameter 114 mm

Height 100 mm

0.63 kg

ELECTRICAL

phase-cut dim


220 - 240 V

Total connected power 7.9 W


PC1

Safety distance 0.3 m


^a RAL Palette colors may deviate slightly due to production conditions.



Cylindrical ceiling surface mounted downlight made from die-cast aluminium; surface Signal White; powder coated; matt texture; RAL 9003; optional single inner reflector and single inner cover available; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; phase-cut dim; light colour 3000 K; Binning initial 3 MacAdam; CRI 80; 220 - 240 V; degree of protection IP65; PC1; light source replaceable by end-user;



LIGHT DISTRIBUTION



[735364W4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

RAY

OUTDOOR 1.0

735364W4

CONE DIAGRAM

flood 32°

h (m)	EO ² (lx)	ø (m)
1	1352	0.58
2	338	1.16
3	150	1.74
4	84	2.32
5	54	2.90

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.95	0.9	0.85	0.8	0.76
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Single Inner Cover

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
RAY max. 10W	Black	ø67·54	9 1 1 0 4 1 B 1
RAY max. 10W	Grey	ø67·54	9 1 1 0 4 1 D 1
RAY max. 10W	White	ø67·54	9 1 1 0 4 1 W 1