


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-B	WEIGHT:0.325kg/m
DIM.: 11.5*21mm	SPEC.:
MFR.:	SUR.:11.5*1000mm
	PROTECTION ANGLE:/

DATA OF LAMP		PHOTOMETRIC DATA			
		Eff: 6.02 lm/W			
MODEL	5050	Imax(cd)	9.169	S/MH(C0/180)	1.25
NOMINAL POWER(W)	4.09	LOR(%)	98.5	S/MH(C90/270)	1.19
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	24.637	η UP,DN(C0-180)	0.0,46.1
NOMINAL FLUX(lm)	25	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,52.5
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	η down(%)	98.5	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:shan
Test Date:2018-09-27

γ Range: 0 - 180DEG
 γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity:45.0%
Test Distance:6.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	Φ lum, lamp
10	9.005	8.891	8.841	8.871	8.918	9.088	9.113	9.075	0- 10	0.8644	0.8644	3.51,3.46
20	8.501	8.352	8.217	8.279	8.368	8.681	8.687	8.677	10- 20	2.474	3.339	13.6,13.4
30	7.670	7.482	7.279	7.363	7.496	7.963	7.913	7.951	20- 30	3.734	7.073	28.7,28.3
40	6.544	6.352	6.101	6.187	6.382	6.893	6.961	6.942	30- 40	4.466	11.54	46.8,46.2
50	5.177	4.986	4.722	4.792	5.019	5.567	5.709	5.668	40- 50	4.559	16.10	65.3,64.4
60	3.623	3.454	3.240	3.281	3.528	4.081	4.105	4.173	50- 60	4.001	20.10	81.6,80.4
70	2.001	1.861	1.715	1.725	1.961	2.491	2.600	2.588	60- 70	2.890	22.99	93.3,92
80	0.4106	0.3428	0.3038	0.2725	0.4482	0.9303	1.136	1.023	70- 80	1.434	24.42	99.1,97.7
90	0	0	0	0	0	0	0.0569	0.0046	80- 90	0.2134	24.64	100,98.5
100	0	0	0	0	0	0	0	0	90-100	0.0006	24.64	100,98.5
110	0	0	0	0	0	0	0	0	100-110	0	24.64	100,98.5
120	0	0	0	0	0	0	0	0	110-120	0	24.64	100,98.5
130	0	0	0	0	0	0	0	0	120-130	0	24.64	100,98.5
140	0	0	0	0	0	0	0	0	130-140	0	24.64	100,98.5
150	0	0	0	0	0	0	0	0	140-150	0	24.64	100,98.5
160	0	0	0	0	0	0	0	0	150-160	0	24.64	100,98.5
170	0	0	0	0	0	0	0	0	160-170	0	24.64	100,98.5
180	0	0	0	0	0	0	0	0	170-180	0	24.64	100,98.5
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:shan
Test Date:2018-09-27


γ Range: 0 - 180DEG
 γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity:45.0%
Test Distance:6.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE:/	WEIGHT:0.325kg/m
DIM.: 11.5*21mm	SPEC.:
MFR.:	SUR.:11.5*1000mm
	PROTECTION ANGLE:/

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	Coefficients of Utilization(CU)															
0.0	1.17	1.17	1.17	1.15	1.15	1.15	1.09	1.09	1.09	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.03	.99	.96	1.01	.97	.94	.97	.94	.91	.93	.91	.88	.90	.88	.86	.84
2.0	.90	.84	.78	.89	.83	.78	.85	.80	.76	.82	.78	.74	.79	.75	.72	.70
3.0	.80	.72	.65	.78	.71	.65	.75	.69	.64	.72	.67	.63	.70	.65	.62	.59
4.0	.71	.62	.56	.69	.61	.55	.67	.60	.54	.65	.59	.54	.62	.57	.53	.51
5.0	.63	.54	.48	.62	.54	.48	.60	.53	.47	.58	.52	.47	.56	.51	.46	.44
6.0	.57	.48	.42	.56	.48	.42	.54	.47	.41	.53	.46	.41	.51	.45	.41	.39
7.0	.52	.43	.37	.51	.43	.37	.49	.42	.37	.48	.41	.36	.47	.41	.36	.34
8.0	.47	.39	.33	.46	.39	.33	.45	.38	.33	.44	.37	.33	.43	.37	.32	.31
9.0	.43	.35	.30	.43	.35	.30	.42	.34	.30	.40	.34	.29	.39	.34	.29	.27
10.0	.40	.32	.27	.39	.32	.27	.38	.32	.27	.37	.31	.27	.37	.31	.27	.25

2



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:shan
Test Date:2018-09-27

γ Range: 0 - 180DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity:45.0%
Test Distance:6.950m [K=1.0000]
Remarks:

WEC AND CCEC

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE: /	WEIGHT: 0.325kg/m
DIM.: 11.5*21mm	SPEC.: SERIAL No.:
MFR.:	SUR.: 11.5*1000mm PROTECTION ANGLE: /

pcc	80%			70%			50%			30%			10%			0	
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.287	.163	.052	.280	.160	.051	.267	.153	.049	.255	.147	.047	.244	.142	.046		
2.0	.275	.151	.046	.269	.148	.046	.258	.143	.045	.247	.139	.043	.238	.134	.042		
3.0	.257	.137	.041	.252	.135	.041	.242	.131	.040	.233	.127	.039	.224	.124	.038		
4.0	.239	.124	.037	.234	.123	.036	.225	.119	.036	.217	.117	.035	.209	.114	.035		
5.0	.222	.113	.033	.218	.112	.033	.210	.109	.032	.202	.107	.032	.195	.104	.031		
6.0	.207	.104	.030	.203	.102	.029	.196	.100	.029	.189	.098	.029	.183	.096	.029		
7.0	.193	.095	.027	.189	.094	.027	.183	.093	.027	.177	.091	.026	.172	.089	.026		
8.0	.180	.088	.025	.177	.087	.025	.172	.086	.024	.166	.084	.024	.161	.083	.024		
9.0	.169	.082	.023	.167	.081	.023	.162	.080	.023	.157	.079	.022	.152	.077	.022		
10.0	.159	.076	.021	.157	.076	.021	.152	.075	.021	.148	.074	.021	.144	.072	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.188	.188	.188	.160	.160	.160	.110	.110	.110	.063	.063	.063	.020	.020	.020	
1.0	.176	.154	.134	.151	.132	.115	.103	.091	.080	.059	.053	.046	.019	.017	.015	
2.0	.168	.130	.098	.144	.112	.085	.099	.077	.059	.057	.045	.035	.018	.015	.011	
3.0	.160	.113	.074	.138	.097	.065	.094	.067	.045	.055	.039	.027	.018	.013	.009	
4.0	.153	.099	.058	.131	.086	.051	.090	.060	.036	.052	.035	.021	.017	.011	.007	
5.0	.146	.089	.047	.125	.077	.041	.086	.054	.029	.050	.032	.017	.016	.010	.006	
6.0	.139	.081	.039	.119	.070	.034	.082	.049	.024	.048	.029	.014	.015	.009	.005	
7.0	.132	.074	.033	.114	.064	.029	.079	.045	.020	.046	.026	.012	.015	.009	.004	
8.0	.126	.068	.029	.108	.059	.025	.075	.042	.018	.044	.025	.011	.014	.008	.003	
9.0	.120	.063	.025	.103	.055	.022	.072	.039	.016	.042	.023	.009	.014	.007	.003	
10.0	.115	.059	.022	.099	.051	.019	.069	.036	.014	.040	.021	.008	.013	.007	.003	

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: shan
Test Date: 2018-09-27

γ Range: 0 - 180DEG
γ Interval: 2.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity: 45.0%
Test Distance: 6.950m [K=1.0000]
Remarks:

Uncorrected UGR Table

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE: /						WEIGHT: 0.325kg/m				
DIM.: 11.5*21mm						SPEC.:		SERIAL No.:		
MFR.:						SUR.: 11.5*1000mm			PROTECTION ANGLE: /	
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions						Viewed crosswise				
x = 2H y = 2H						Viewed endwise				
3H						11.3	12.8	11.6	13.0	13.2
4H						12.5	13.9	12.8	14.1	14.4
6H						12.9	14.2	13.2	14.5	14.7
8H						13.0	14.2	13.3	14.5	14.8
12H						12.9	14.1	13.3	14.4	14.7
4H						12.9	14.0	13.2	14.3	14.6
2H						10.8	12.3	11.1	12.5	12.7
3H						11.9	13.3	12.2	13.5	13.8
4H						12.2	13.5	12.5	13.8	14.0
6H						12.3	13.5	12.6	13.8	14.0
8H						12.2	13.4	12.6	13.7	14.0
12H						12.2	13.3	12.5	13.6	13.9
2H						11.8	13.1	12.1	13.3	13.6
3H						13.1	14.3	13.5	14.6	14.9
4H						13.6	14.6	14.0	14.9	15.3
6H						13.7	14.6	14.1	15.0	15.4
8H						13.7	14.5	14.1	14.9	15.3
12H						13.6	14.4	14.1	14.8	15.2
4H						13.7	14.5	14.1	14.9	15.3
6H						13.8	14.5	14.3	14.9	15.4
8H						13.8	14.4	14.3	14.8	15.3
12H						13.8	14.3	14.2	14.7	15.2
4H						13.6	14.4	14.1	14.8	15.2
6H						13.8	14.4	14.3	14.8	15.3
8H						13.8	14.3	14.2	14.8	15.2
Variations with the observer position at spacings:										
S = 1.0H		+ 0.2 / - 0.3				+ 0.3 / - 0.3				
1.5H		+ 0.2 / - 0.3				+ 0.2 / - 0.5				
2.0H		+ 0.5 / - 0.5				+ 0.4 / - 0.5				

CIE Pub.117 Corrected 25.00 lm Total Lamp Luminous Flux. (8log(F/F0) = -12.8)

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: shan
Test Date: 2018-09-27

γ Range: 0 - 180DEG
γ Interval: 2.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity: 45.0%
Test Distance: 6.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE: /	WEIGHT: 0.325kg/m
DIM.: 11.5*21mm	SPEC.: SERIAL No.:
MFR.:	SUR.: 11.5*1000mm PROTECTION ANGLE: /


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) k(RI) x RCR = 5									
k = 0.60	58	47	40	57	46	40	56	46	40	33
0.80	68	57	50	67	56	49	65	55	49	42
1.00	76	66	59	75	65	58	73	66	58	51
1.25	83	73	66	82	73	66	79	71	65	58
1.50	88	79	72	86	78	72	84	76	71	63
2.00	95	87	81	93	86	80	90	83	78	71
2.50	98	91	86	97	90	85	93	87	83	75
3.00	102	95	90	100	94	89	96	91	87	79
4.00	106	100	96	103	98	95	99	95	92	83
5.00	108	103	100	105	101	98	101	98	95	86
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004					Suspended			SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: shan
Test Date: 2018-09-27

γ Range: 0 - 180DEG
 γ Interval: 2.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity: 45.0%
Test Distance: 6.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE: /	WEIGHT: 0.325kg/m
DIM.: 11.5*21mm	SPEC.: SERIAL No.:
MFR.:	SUR.: 11.5*1000mm PROTECTION ANGLE: /




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: shan
Test Date: 2018-09-27

γ Range: 0 - 180DEG
 γ Interval: 2.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity: 45.0%
Test Distance: 6.950m [K=1.0000]
Remarks:

AAI Figure

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE:/	WEIGHT:0.325kg/m
DIM.: 11.5*21mm	SPEC.: SERIAL No.:
MFR.:	SUR.:11.5*1000mm PROTECTION ANGLE:/




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:shan
Test Date:2018-09-27

γ Range: 0 - 180DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity:45.0%
Test Distance:6.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE: /	WEIGHT: 0.325kg/m
DIM.: 11.5*21mm	SPEC.: SERIAL No.:
MFR.:	SUR.: 11.5*1000mm PROTECTION ANGLE: /



C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: shan
Test Date: 2018-09-27

γ Range: 0 - 180DEG
 γ Interval: 2.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity: 45.0%
Test Distance: 6.950m [K=1.0000]
Remarks:

Average Luminance Table(CIBSE)

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE:/	WEIGHT:0.325kg/m
DIM.: 11.5*21mm	SPEC.:
MFR.:	SUR.:11.5*1000mm
	PROTECTION ANGLE:/

Parameter description for average Luminance	Symbol	Value	Unit
Luminance in Azimuth Plane	Bc	refer Table 2	cd/sq.m.
Intensity at angle Gamma in given azimuth plane	I	from data	cd/klm
Number of lamps	N	1	
Output of each lamp(initial lumens as specified)	F	25	lm
Multiplying factor	K	1	
Luminous area in horizontal plane used in calculations	A	0.0115	sq.m.
Angle to the downward vertical from light centre	Gamma	from data	deg

Table 1. Calculation parameters for determination of CIBSE LG3:1996 Average Luminance

G	C plane(deg)																			
deg	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	
55	669	659	651	646	644	642	639	627	615	605	605	609	613	611	611	613	623	636	651	
60	630	619	611	604	602	600	597	586	573	563	564	567	572	569	568	570	581	595	614	
65	579	566	556	548	547	546	544	533	521	510	509	511	514	512	512	515	527	544	564	
70	509	495	484	476	474	473	471	459	447	436	436	438	441	437	434	437	452	473	499	
75	400	383	370	362	361	362	362	351	339	328	328	330	332	326	322	324	344	371	401	
80	206	187	174	167	169	173	177	170	161	152	148	144	141	133	128	131	155	186	224	
85	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	

Table 2. Average Luminance(cd/sq.m.) for defined C plane,Gamma angle

CIBSE Category	Gamma (deg)	Average Luminance		Patch Luminance	
		maximum	specified	maximum	specified
		calculated	maximum	measured	maximum
Category 1	55 to 90	669	200	---	500
Category 2	65 to 90	579	200	---	500
Category 3	75 to 90	401	200	---	500

Table 3. Tabulation of Average and Patch Luminance(cd/sq.m.) for defined CIBSE categories

No match

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:shan
Test Date:2018-09-27

γ Range: 0 - 180DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity:45.0%
Test Distance:6.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: C-SFR-F15A-HB-D24CV-RGB-60-5050-1M-BTYPE: /	WEIGHT: 0.325kg/m
DIM.: 11.5*21mm	SPEC.: SERIAL No.:
MFR.:	SUR.: 11.5*1000mm PROTECTION ANGLE: /

Table--1

UNIT: cd

C(°)	0	30	60	90	120	150	180	210	240	270	300	330						
γ (°)	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85
0	9.14	9.14	9.14	9.14	9.14	9.14	9.14	9.14	9.14	9.14	9.14	9.14						
5	9.13	9.08	9.07	9.06	9.07	9.06	9.09	9.13	9.16	9.16	9.15	9.14						
10	9.01	8.92	8.87	8.84	8.88	8.86	8.92	9.05	9.12	9.11	9.08	9.07						
15	8.85	8.76	8.65	8.62	8.69	8.65	8.74	8.91	9.03	8.99	8.97	8.93						
20	8.50	8.43	8.28	8.22	8.30	8.26	8.37	8.57	8.79	8.69	8.72	8.64						
25	8.21	8.12	7.95	7.90	7.98	7.92	8.06	8.31	8.57	8.38	8.47	8.37						
30	7.67	7.56	7.40	7.28	7.39	7.34	7.50	7.79	8.14	7.91	8.03	7.88						
35	7.25	7.14	6.99	6.84	6.94	6.91	7.08	7.38	7.78	7.58	7.67	7.49						
40	6.54	6.41	6.29	6.10	6.19	6.18	6.38	6.70	7.09	6.96	7.06	6.83						
45	6.02	5.89	5.78	5.56	5.66	5.64	5.85	6.20	6.56	6.49	6.60	6.33						
50	5.18	5.02	4.95	4.72	4.79	4.79	5.02	5.40	5.74	5.71	5.82	5.52						
55	4.56	4.41	4.37	4.14	4.19	4.20	4.45	4.81	5.15	5.12	5.24	4.93						
60	3.62	3.47	3.43	3.24	3.29	3.28	3.53	3.91	4.26	4.11	4.34	4.01						
65	2.98	2.82	2.81	2.63	2.66	2.66	2.91	3.26	3.66	3.47	3.72	3.38						
70	2.00	1.87	1.85	1.72	1.73	1.72	1.96	2.29	2.70	2.60	2.77	2.41						
75	1.35	1.23	1.23	1.12	1.14	1.12	1.34	1.59	2.08	2.00	2.14	1.76						
80	0.41	0.33	0.35	0.30	0.28	0.26	0.45	0.70	1.17	1.14	1.22	0.83						
85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.17	0.59	0.62	0.65	0.27						
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.01	0.00						
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00						

C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: shan
Test Date: 2018-09-27

γ Range: 0 - 180DEG
γ Interval: 2.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V1.0.257
Humidity: 45.0%
Test Distance: 6.950m [K=1.0000]
Remarks: